

<b>Specifications:</b>		
<b>Model No.</b>	YC-1880CL	
<b>Printhead</b>	XP600	
<b>Number of printhead</b>	1	
<b>Color</b>	4 Color (C- M- Y- K)	
<b>Printing Resolution</b>	1440dpi	
<b>Print Width</b>	1870	
<b>Print Speed</b>	<b>Draft mode</b>	30 sq. m./h
	<b>Production</b>	25 sq. m./h
	<b>Quality mode</b>	20 sq. m./h
<b>Ink</b>	waterbased. Eco-solvent, sublimation	
<b>Ink Capacity</b>	440ml Continuous Ink Supply Cartridge * 8 pcs or CISS optional	
<b>Media</b>	PVC, PP, Vinyl, flex, one way vision, frontlit, backlit, car wraps, sticker,Mesh...	
<b>Water-based materisl</b>	PP/Backlit film/ Photo paper/ Movable self-adhesive vinyl/ Pictorial cloth	
<b>Eco-slovent materials</b>	Car sticker/ Lamp cloth/ Face film/ Coated banner/ Flag cloth	
<b>printing materials</b>	Thermal transfer paper/ Pure cotton	

<b>Special materials</b>	Wallpaper/ Canvas/Chinese art paper/ Grid cloth
<b>Media handing</b>	Roll to roll, sheet to sheet
<b>Heating System</b>	Front, middle, back three sections heating system, PID temperature controller
	Adjustable range: room temperature~80°C
<b>Drying system</b>	Fans cooler
<b>Rip Software</b>	Main top, Ultra print, photo print
<b>Color management</b>	ICC or Density Curve
<b>Image format</b>	Bmp, TIF, Jpg, Pdf...
<b>Driver</b>	Professional bi-language software (Chinese & English)
<b>Interface</b>	USB 2.0, RS 232
<b>Operation System</b>	WinXP, Win7
<b>Input Power</b>	AC 220-240V 50/60 HZ 15A
<b>Working Environment</b>	Temperature:20-25 °C, Humidity: 40%-70%
<b>Machine size/ weight</b>	2820*730*630mm
	165±5%KG
<b>packaging size/ weight</b>	2870*780*1260mm
	245±5%KG