

Specifications:		
Model No.	YC-1880VL	
Printhead	XP600	
Number of printhead	1	
Color	4 Color (C- M- Y- K)	
Printing Resolution	1440dpi	
Print Width	1870	
Print Speed	Draft mode	30 sq. m./h
	Production	25 sq. m./h
	Quality mode	20 sq. m./h
Ink	waterbased. Eco-solvent, sublimation	
Ink Capacity	440ml Continuous Ink Supply Cartridge * 8 pcs or CISS optional	
Media	PVC, PP, Vinyl, flex, one way vision, frontlit, backlit, car wraps, sticker,Mesh...	
Water-based materisl	PP/Backlit film/ Photo paper/ Movable self-adhesive vinyl/ Pictorial cloth	
Eco-slovent materials	Car sticker/ Lamp cloth/ Face film/ Coated banner/ Flag cloth	
printing materials	Thermal transfer paper/ Pure cotton	

Special materials	Wallpaper/ Canvas/Chinese art paper/ Grid cloth
Media handing	Roll to roll, sheet to sheet
Heating System	Front, middle, back three sections heating system, PID temperature controller
	Adjustable range: room temperature~80°C
Drying system	Fans cooler
Rip Software	Main top, Ultra print, photo print
Color management	ICC or Density Curve
Image format	Bmp, TIF, Jpg, Pdf...
Driver	Professional bi-language software (Chinese & English)
Interface	USB 2.0, RS 232
Operation System	WinXP, Win7
Input Power	AC 220-240V 50/60 HZ 15A
Working Environment	Temperature:20-25 °C, Humidity: 40%-70%
Machine size/ weight	2820*730*630mm
	165±5%KG
packaging size/ weight	2870*780*1260mm
	245±5%KG